

Declaration of Performance

No. 0231396701150

1. Product Type

Unique identification code of the product-type:

NovoProof®

2. Type

Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

DA, thickness 1,5 mm

3. Intended use

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Elastomeric sheet for structural waterproofing made of ethylene propylene diene terpolymer (EPDM) without fleece-backing acc. to EN 13967 damp proof sheets (Type A) basement tanking sheets (Type T)

4. Name, registered trade name

Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**NovoProof®
CQLT SaarGummi Deutschland GmbH
Eisenbahnstraße 24
D-66687 Wadern-Büschfeld
GERMANY**

5. System for the evaluation of performance stability

System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 2+

6. Notified body

In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**1213
Notified factory production control certification body No. 1213 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control, 1213-CPR-023**

7. Declared performance

Essential characteristics	Performance	Test standard	Harmonised technical specification
Water tightness	passed	EN 1928 B	EN 13967:2012
Resistance to static loading	> 20 kg	EN 12730 B	
Durability of watertightness against ageing	passed	EN 1296 EN 1928	
Effects of liquid chemicals, including water (23°C/28 d)	passed	EN 1847	
Tear resistance	≥ 120 N	EN 12310-1	
Joint shear resistance (hot-air or hot-wedge welding)	Fracture outside the joint or ≥ 250 N/50 mm	EN 12317-2	
Resistance to impact	≥ 2000 mm	EN 12691 B	
Tensile strength	≥ 8,5 N/mm ²	EN 12311-2 B	
Elongation (500 mm/min)	≥ 350%	EN 12311-2 B	
Reaction to fire	Class E	EN ISO 11925-2 EN 13501-1	
Hazardous substances	-	-	

The performance of the above product is in conformity with the declared performance. The manufacturer referred to above is solely responsible for drawing up the declaration of performance in accordance with Regulation (EU) No 305/2011.

Signed for and on behalf of the manufacturer by:
Wadern-Büschfeld, 01.03.2022


Piotr Gaska
 Managing Director